



PATENT ABSTRACTS OF JAPAN

(11) Publication number: 10026934 A

(43) Date of publication of application: 27.01.98

(51) Int. Cl. G09F 3/00
B42D 15/10
G06K 19/077
G06K 19/07

(21) Application number: 08183444

(22) Date of filing: 12.07.96

(71) Applicant TOSHIBA CHEM CORP

(72) Inventor: FURUHASHI JUN

(54) ELECTRONIC TAG AND ITS MANUFACTURING METHOD

(57) Abstract

PROBLEM TO BE SOLVED: To easily obtain a sheathing resin which has high mechanical strength and excellent environmental resistance in an electronic tag in which internal parts such as IC chips and an antenna are necessary to be protected by the sheathing resin.

the movement of the internal parts by the pressure of the resin at the time of molding the external ornamental part can be prevented to improve productivity.

COPYRIGHT: (C)1998, JPO

SOLUTION: An internal parts holding parts 33 having a recessed part 33a for housing the internal parts and a projection 35 for positioning in a metallic mold is prepared, the internal parts are housed in the recessed part 33a and, then, the resin is injected in the recessed part and is solidified to form a protective fixing layer 35 for protecting and fixing the internal parts and, further, an external ornamental part is molded by the metallic mold so as to envelop the internal parts holding parts. Since both the protective fixing layer and the external ornamental part protect the internal parts, the protective fixing layer prevent the internal parts from being in contact with moisture even in the case of moisture immersion to inside from minute cracks, etc., generated in the external ornamental part. Further, since the internal parts housed in the recessed part in the internal parts holding parts are fixed by the protective fixing layer,

